



US005354482A

United States Patent [19]

[11] Patent Number: 5,354,482

Varadi

[45] Date of Patent: Oct. 11, 1994

[54] **PROCESS AND APPARATUS FOR
OXIDIZING INDUSTRIAL SPENT CAUSTIC
AND EFFECTING GAS-LIQUID MASS
TRANSFER AND SEPARATION**

[75] Inventor: **Tamas Varadi**, Houston, Tex.

[73] Assignee: **Merichem Company**, Houston, Tex.

[21] Appl. No.: **59,454**

[22] Filed: **May 7, 1993**

[51] Int. Cl.⁵ **C02F 1/74**

[52] U.S. Cl. **210/742; 210/744;
210/758; 210/765; 210/761; 55/228; 95/187;
95/188**

[58] **Field of Search** **210/742, 744, 758, 765,
210/766, 741, 761; 55/228; 95/187, 188, 189**

[56] **References Cited**

U.S. PATENT DOCUMENTS

2,560,978	7/1951	Persson et al.	210/758
2,869,844	1/1959	Thomas	261/21
3,178,260	4/1965	Tirado	210/758
3,963,611	6/1976	Dardenne-Ankringa, Jr.	210/758
3,977,829	8/1976	Clonts	23/267
3,992,156	11/1976	Clonts	23/267
4,347,226	8/1982	Audeh et al.	210/761
4,350,599	9/1982	Chowdhury	210/761
4,384,959	5/1983	Bauer et al.	210/739
4,666,689	5/1987	Maple et al.	423/183
4,675,100	6/1987	Maple et al.	208/203
4,812,243	3/1989	Brandenburg et al.	210/761

5,082,571 1/1992 Beula et al. 210/761

OTHER PUBLICATIONS

J. D. Martin and L. D. Levanas, "Air Oxidation of Sulfide in Process Water", *Division of Refining*, vol. 42, pp. 392-398 (1962).

F. J. Suarez, "Safe Waste Caustic Disposal", *Hydrocarbon Technology International* 1989/1990.

M. R. Beychok, *Aqueous Wastes from Petroleum and Petrochemical Plants*, (2nd Ed. 1973 John Wiley & Sons) pp. 156-266.

Primary Examiner—Neil McCarthy

Attorney, Agent, or Firm—Jennifer S. Sickler

[57] ABSTRACT

An improved process for oxidizing industrial spent caustic streams, whereby oxidation of spent caustic occurs in a unitary processing tower with three chambers that cooperate simultaneously to oxidize the caustic in the first chamber; to separate the caustic from the oxidizing gas in the second chamber; and, in the third chamber, to pass gas and cooled caustic through a mass transfer apparatus that cools and cleans the gas and releases the caustic and gas into a gas-liquid separation zone of the upper chamber. An alternative embodiment of the invention involves spatially separating the upper chamber from the other two chambers.

20 Claims, 3 Drawing Sheets

